

MK1500DP-EFS

Height	Stand alone mount 41" (104 cm) Engine room mount 41" (104 cm) plus mount
Width	Stand alone mount 28.64" (71 cm) Engine room mount 22" (56 cm)
Depth	Stand alone mount 27" (68.58 cm) Engine room mount 22" (56 cm)
Service Clearance	14" (35.56 cm) above 4" (10.16 cm) below
Weight	160 lbs (73 kg) Varies with mount and pump type
Inlet and out ports	#24 J1926 ORB or 1-1/2" NPT 6405 adapter
Fuel	Diesel
Max Fuel Flow	1500gph (5678 lt/h)
Max Operating Pressure	50 psi (3.4 bar)
Normal Operating Vacuum	0-6 in Hg (20 kPa)
Vacuum Alarm	8" \pm 2" in Hg (27 \pm 7 kPa)
Vacuum Sensor (optional)	4-20 ma
Pressure Sensor (optional)	4-20 ma
Bowl Water Alarm Capacity	50 oz. (1.5 L)
Water Removal	99%
Voltage	12 VDC <i>Use 24v to 12v inverter for 24v systems</i>
Fill pump Pressure Voltage	Marco UP2 15 psi (1 bar) 12 vdc
Control voltage DC circuit protection	5 amp
Pump AC circuit protection	20 amp
Polishing Pump Varies on pump selection Psi Flow Max lift Motor	Oberdorfer N990 5-50 psi (.34 - 3.44b ar) 1400 gph (5299 lt/hr) 20 feet Leeson 2 hp 115 volts AC
Replacement element	Racor FBO Aquabloc 3D 10 Micron 60363
Control panel	KP600