

MK240DP-EFS TECHNICAL SPECIFICATIONS (PANEL MOUNT)

Height	22.85" (58 cm)
Width	13.5" (34 cm) filter 16" (40.6 cm) mount panel 18.68" (47.4 cm)
Depth	8.48" (21.5 cm)
Service Clearance	10" (25.4 cm) 2" (5.1 cm) below
Weight	44 lbs (20kg)
Inlet and out ports	#14 Orb 1-3/16 or 3/4" female NPT adapter (standard)
Fuel	Diesel
Max Fuel Flow	240 gph (908 L/h)
Max Operating Pressure	40 psi (2.1 bar)
Normal Operating Vacuum	0-6 in Hg (20 kPa)
Vacuum Alarm	8" \pm 2" in Hg (27 \pm 7 kPa)
Optional transducer	4-20 ma
Bowl Water Alarm Capacity	10.3 ounces (.3 L)
Water Removal	99%
Voltage	12 VDC
Current Draw- Pump	10 amps max
Circuit Protection	10 amp
Pump	Marco
Psi	15 psi (1 bar)
Flow	240 gph (908)
<i>Recommended</i> Replacement elements -Racor®	2 micron 2020SM-OR 10 micron 2020TM-OR 30 micron 2020PM-OR

