


MK60DP/K60DP TECHNICAL SPECIFICATIONS

Height	12.83" (32.5 cm)
Width	14.64" (37 cm) filter 12.75" (32.3 cm) mount panel
Depth	7.04" (17.9 cm)
Service Clearance	5" (12.7 cm) above 2" (5.1 cm) below
Weight	19.2lbs (8.7 kg)
Inlet and out ports	#10 Orb 7/8-14 or 1/2" NPT
Fuel	Diesel
Max Fuel Flow	60 gph (227 lt/h)
Max Operating Pressure	30 psi (2.1 bar)
Normal Operating Vacuum	0-6 in Hg (20 kPa)
Vacuum Alarm	8" ± 2" in Hg (27 ± 7 kPa)
Bowl Water Alarm Capacity	5.5 oz. (163 ml)
Water Removal	99%
Voltage	12 VDC <i>Use 24v to 12v inverter for 24v systems</i>
Current Draw- Standby Warning EFS CYCLE Pump	76 ma 175 ma 300 ma 2.3 amps max
Circuit Protection	5 amp
Pump Psi Flow Duty Life Run dry	Walbro FRB13-2 6.0 to 8.0 psi (.41 - .55 bar) 60gph (227 lt/hr) 18000 + hrs Four (4) hours
<i>Recommended</i> Replacement elements -Racor® 	2 micron 2010SM-OR 10 micron 2010TM-OR 30 micron 2010PM-OR
<i>Recommended</i> 2 x 12 MM BUNA O-RING (T-Handle)	KTI P/N KAOR2MM12

